sperita
engineering surfaces

SOLIDX
SERIES

800X**2400MM** | 800X**3000MM**

15MM
THICKNESS

sperita
engineering surfaces

ABOUT
COMPANY

The strength and success of Sperita Granito lie in its sound infrastructure which has advanced manufacturing facilities that comprise the latest machinery and advent-grade technologies.
The ultra-modern plant supported and run by technically sound staff ensures that Sperita Granito is indeed matchless when it comes to ceramic tilling solutions.

Sperita Granito has developed in leaps and bounds by getting into the greater pool of technology, by adopting italian technology which has benefitted customers in all arenas since factors like optimization, calibrations, sizing, and designing is taken great care off.
Technology providers in the ceramics field who realized the potential & sincerity of the company preferentially offered us and distributors the best support to strengthen individual positions in our respective markets.

www.sperita.in









Built on a foundation of advanced technology and precision engineering, our manufacturing process ensures consistent quality, superior strength, and flawless finishes—delivering surfaces that meet the highest standards of performance and design.

SOLIDX SERIES

ARCHITECTURE AT IN **EXPRESSION.**

A bold expression of modern architecture, where design meets precision engineering. Each surface is crafted to deliver refined textures, lasting durability, and a seamless visual flow—elevating spaces with timeless sophistication.

Inspired by contemporary aesthetics and built with advanced technology, these surfaces bring strength, elegance, and versatility to both residential and commercial environments.

Italian Technology

FULL BODY
SERIES

VIP
वाली
Feeling

800X2400MM | 800X3000MM

15MM THICKNESS

Built with a solid 15MM thickness and available in expansive slab formats, these surfaces are designed to deliver strength, scale, and seamless architectural elegance.



ENDLESS DESIGN POSSIBILITIES

Multiple edge profiles
crafted to enhance both aesthetics and functionality

Engineered with precision and inspired by Italian technology, our surfaces offer a wide range of edge and joint possibilities to suit every architectural need. From sharp modern lines to smooth rounded finishes, each detail is designed to ensure seamless integration, superior strength, and refined visual appeal across residential and commercial spaces.

CONTINUA+ ITALIAN TECHNOLOGY



Squared Ridge at 45° | Rounded Ridge at 45° | Straight Squared ridge | Rounded Straight ridge | Double straight Squared ridge | Double straight Rounded ridge

JOINT POSSIBILITIES



Birds beak | 45° corner | Soft corner

www.sperita.in

CRAFTED FOR
CULINARY SPACES

Designed with a solid 15MM structure and expansive slab formats, these surfaces offer durability, hygiene, and seamless performance— perfectly suited for modern kitchens where design meets everyday functionality.



Designed to impress endlessly



Size_
800x2400mm



Size_
800x3000mm



Surfaces_
Matt, Polished

Thickness_
15mm

Type_
Fullbody

EVERYDAY **PERFORMANCE, REFINED**

- Water Resistant Surface
- Hygienic and Suitable for Contact with Food
- Resistant to UV Rays
- Impact Resistant Surface
- Resistant to Mould, Mildew, and Fungus

ADVANCED SURFACE **PROTECTION**

- Stain Resistant Surface
- Resistant to Fire and Heat
- Frost Resistant Surface
- Flatness and Stability Over Time
- Scratch and Abrasion Resistant
- Easy to Clean Surface
- Resistant to Chemicals, Acids, Bases, and Solvents

ENDLESS DESIGN POSSIBILITIES

MULTIPLE EDGE PROFILES
CRAFTED TO ENHANCE BOTH AESTHETICS AND FUNCTIONALITY

Engineered with precision and inspired by Italian technology, our surfaces offer a wide range of edge and joint possibilities to suit every architectural need. From sharp modern lines to smooth rounded finishes, each detail is designed to ensure seamless integration, superior strength, and refined visual appeal across residential and commercial spaces.

APPLICATION AREAS

- Countertop
- Dining tabletop
- Lift Frame
- Bathroom
- Worktop
- Elevation
- Staircase
- Window & Door Frame
- Basin & Furniture
- Fireplace
- Wall Cladding
- Floor Covering

COLOUR PERFECTED



sperita
engineering surfaces

Full Body Excellence Crafted for
Lasting Performance.

SOLIDX SERIES





SOLID BROWN

800X2400mm | 800X3000mm

Surface - **Matt / Glossy**
Type - **Full Body**
Thickness - **15**



SOLID FOSSIL GREY

800X2400mm | 800X3000mm

Surface - **Matt / Glossy**
Type - **Full Body**
Thickness - **15**



SOLID KOTTA

800X2400mm | 800X3000mm

Surface - **Matt / Glossy**
Type - **Full Body**
Thickness - **15**

SOLID X SERIES

Pure Color. Solid Strength.
Timeless Performance.



TOUCH FOR 360°

SOLID FOSSIL GREY

SOLID KOTTA

TOUCH FOR 360°

sperita
engineering surfaces

Engineered Full Body Tiles
with Lasting Integrity.

SOLIDX SERIES



SOLID BLACK

800X2400mm | 800X3000mm

Surface - **Matt / Glossy**
Type - **Full Body**
Thickness - **15**



sperita
engineering surfaces

Where Full Body
Strength Meets Refined Simplicity.

SOLIDX SERIES

SOLID WHITE

800X2400mm | 800X3000mm

Surface - **Matt / Glossy**
Type - **Full Body**
Thickness - **15**



SOLID SCABAS

800X2400mm | 800X3000mm

Surface - **Matt / Glossy**
Type - **Full Body**
Thickness - **15**



SOLID STEEL GREY

800X2400mm | 800X3000mm

Surface - **Matt / Glossy**
Type - **Full Body**
Thickness - **15**



SOLIDX SERIES

Full Body Tiles Defined by
Strength & Purity.



TOUCH FOR 360°

SOLID SCABAS

SOLID STEEL GREY

TOUCH FOR 360°

sperita
engineering surfaces

Strength at the Core,
Style on the Surface.

SOLIDX SERIES





SOLID VERDE

800X2400mm | 800X3000mm

Surface - **Matt / Glossy**
Type - **Full Body**
Thickness - **15**

MANUALLY TRANSPORTING SLAB

Only for 1/4" Slabs

MOVING A SLAB





RAISING A IMMODERATE SLAB ONTO A BENCH



✕ INCORRECT



✓ CORRECT

HANDLING IMMODERATE SLAB FOR WALL



✕ INCORRECT



✓ CORRECT

WORKING WITH THE VARIOUS VERSIONS OF SLAB

CUTTING WITH DIAMOND DISCS





Our products can be cut using diamond discs fitted onto the hand-held electrical grinding machine. The speed of Disc rotation must be high (>10000 RPM) and should have a low feed rate (<1 m/min). It may be required to cool the disc with water. Recommended discs are the thin types generally used for cutting porcelain stoneware. The surface should be kept on a FLAT base while cutting without any gap underneath.

DRILLING





You can use cutting discs fitted to battery-operated screwdrivers or angle grinders, or electrical drills as an alternative.

INTERNAL CUT/L-SHAPED CUT



To get internal and L-shaped corners & to reduce the risk of breakage, cut 'o' at the vertex of the internal corners using bits with a radius of at least 5mm. Then cut with diamond discs, be cautious to stop moving the cutting tool forward. To drill and cut using diamond discs, and more follow the instructions provided below

When using these tools:

- Cool the point being drilled with water
- Dont put too much pressure and bear in mind the resistance of the type of laminated stoneware you are working on
- If you are using tungsten bits, start drilling at a low speed
- If you are using drills or screwdrivers, do not select hammering mode

EDGE-FINISHING







INSTRUCTIONS FOR MANUAL INSTALLATION

SINGLE LAYER METHOD



DOUBLE LAYER METHOD



COMPRESSING THE TILE



IMPORTANT

All cutout corners must have a minimum diameter of 1/4". Never leave 90° angles. We recommend radiuses of more than 1/4" when the kitchen design allows as it eases the countertop fitter.



CLEANING & MAINTENANCE

Our products are non porous (due to their high quality raw materials, stringent production parameters and state of the art technology), hence any dust or deposited waste cannot penetrate the surface.

For most cases only a damp cloth is sufficient for cleaning.

Regular cleaning highlights the aesthetic features of the surface and gives it exceptional shine.

For highly aggressive cleaning caused by some common food and substances follow the table below.

TYPE OF STAIN	CHEMICAL PRODUCT	EXAMPLE
Grease	Alkaline - Solvent	Detergent
Oil	Solvent	Ammonia, Backing Soda
Ink	Oxidant - Solvent	Alcohol, Liquid Bleach, Nail Paint Remover
Rust	Acid	Hydrochloric Acid, Vinegar, Red Harpic
Lime	Acid	Descaling Reagent, Hydro Chloric Acid
Cement	Acid	Hydro Chloric Acid
Wine	Alkaline	Ammonia, Liquid Bleach
Coffee	Alkaline - Solvent	Ammonia, Liquid Bleach
Rubber	Solvent	Alcohol, Thinner
Plaster	Acid	Hydro Chloric Acid
Candle Wax	Solvent	Alcohol, Thinner
Iodine	Oxidant	Liquid Bleach
Blood	Oxidant	Liquid Bleach
Ice Cream	Alkaline	Liquid Bleach

Note: It is recommended that any kind of stain needs to get clean immediately / as soon as possible.

TECHNICAL SPECIFICATIONS

CHARACTERISTIC	STANDARD AS PER ISO-13006/2018 En14411 gr.bla	VALUE	TEST METHOD
Regulatory Properties			
Deviation in Length & Width	±0.5%	±0.2%	ISO 10545-2
Deviation in Thickness	±5%	±5%	ISO 10545-2
Straightness of Sides	±0.5%	±0.2%	ISO 10545-2
Rectangularity	±0.5%	±0.2%	ISO 10545-2
Surface Flatness	±0.5%	±0.3%	ISO 10545-2
Colour Difference	△E ≤ 1.00	△E ≤ 0.30	ISO 10545-16
Glossiness	As per Mfg.	As per Mfg.	GlossMeter
Structural Properties			
Water Absorption	≤ 0.5 %	≤ 0.3 %	ISO 10545-3
Apparent Density	As per Mfg.	> 2.20 g/cc	ISO 10545-3
Massive Mechanical Properties			
Modulus of Repture	Min. 35 N/mm²	Min. 40 N/mm²	ISO 10545-4
Breaking Strength	Min. 1300 N	Min. 5000 N	ISO 10545-4
Impact Resistance	As per Mfg.	Min. 0.55	ISO 10545-4
Surface Mechanical Properties			
Surface Abrasion Resistance	As per Mfg.	Min. class 3	ISO 10545-7
Moh's Hardness	As per Mfg.	Min. class 4	BS EN 15771
Thermo Hygrometric Properties			
Frost Resistance	As per Mfg.	Frost Proof	ISO 10545-12
Thermal Shock Resistance	Min. 10 Cycle	Min. 10 Cycle	ISO 10545-9
Moisture Expansion	Max. 0.6 mm/m	Max. 0.02 mm/m	ISO 10545-10
Thermal Expansion	Max. 9.0 × 10^{-6}	Max. 6.0 × 10^{-6}	ISO 10545-8
Chemical Properties			
Chemical Resistance	As per Mfg.	No Damage	ISO 10545-13
Stain Resistance	Resistant	Resistant	ISO 10545-14
Safety Properties			
Slip Resistance	As per Mfg.	N. A.	DIN 51130
Fire Resistance	As per Mfg.	Fire Proof	N. A.

PACKING DETAILS

Dimension (mm)	No. of PC's/Box	Square Feet	Weight (Approx)
800x3000 mm	1 Pcs.	25.83 Sq. Feet	83 Kg.
800x2400 mm	1 Pcs.	20.67 Sq. Feet	68 Kg.

sperita
engineering surfaces

Sperita Granito LLP.

**S. No. 365-Sapar, S. No. 366P1, P2 and 369-Jasmatgadh,
Jetpar Road, Near Sparten Granito PVT LTD,
Jasmatgadh and Sapar, Morbi - 363642, (Guj.) India.**

Domestic: +91 9512400444
Export: +91 95128 91444

info@sperita.in | www.sperita.in

Designing AsquareX

Discover more!